

TECHNICAL SPECIFICATIONS

TB8H		
GNSS ¹	Positioning Technology GPS, BDS, GALILEO, QZSS	
Configuration	OS & Processor Android 13, 2.7GHz, 8 core high-speed processor	
	Storage RAM 6GB, ROM 128GB, SD card 1TB	
	Display 8-inch display, touchable screen	
	Resolution 1920×1200, 450nit, readable under the sun	
	Camera 16M pixels rear camera, 8 M pixels front camera, autofocus, highlight LED flash	
	Built-in Sensor L-sensor (Compatible Design), G-sensor, Gyroscope, E-compass	
	USB USB 2.0, Type-C, OTG function	
Communication	SIM Support dual Nano SIM	
	Network Type 5G: FR1 N1/3/20/28/41/77/78/79 FDD: B1/2/3/4/5/7/8/20/28 TDD: B38/39/40/41 3G: B1/B2/B5/B8 GSM: B2/B3/B5/B8	
	Wi-Fi 802.11 a/b/g/n/ac (2.4 & 5GHz)	
	Bluetooth Bluetooth 5.1, BLE	
	NFC NFC 13.56MHz, work distance ≥ 3cm support ISO/ 14443 A/B, ISO/ 15693, NFC- IP1, NFC-IP2 M1 Card(S50, S70), CPU Card, NFC Label	
	Battery ²	Capacity 15 hours
	Charging time 3 hours	
Physical	Size 236mm*142mm*14mm	
	Weight 636 g (with battery)	
	Humidity 0-95% RH, non-condensing	
	Dustproof & Waterproof IP67, and 1.2m free drop	
	Temperature Working: - 20°C ~ + 60°C; Storage: - 40°C ~ + 70°C	

Descriptions and specifications are subject to change without notice.

1. Optional.

2. The battery operating time is related to the operating environment, operating temperature and battery life.



AUTHORIZED DISTRIBUTION PARTNER

22S102

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555,

North of Panyu RD, Panyu District, 511400 Guangzhou, China.

www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn

CE IP67

TB8H

Rugged Tablet

