

# iHand55

Professional Field Controller



## KEY FEATURES



5.5" sunlight readable display capacitive touch screen for fingers or stylus.



QWERTY full keyboard designed, convenient for different measurement application scenarios.



Equip laser rangefinder(optional) can greatly improve the efficiency of your measurement work.



Android 11 operating system equipped to maintain the productivity of numerous survey projects and data.

## TECHNICAL SPECIFICATIONS

<b>Hardware Configuration</b>	OS	Android 11
	Processor	CPU: 8 core; 2.0 GHZ
	Storage	3GB RAM+32GB ROM(Normal version), 4GB RAM+64GB ROM(Laser version); T-Flash memory card, up to 128GB
	Display	720*1440, 5.5", 500 nit, bright Outdoor Color capacitive multi-touch screen (with touch pen, can be operated with gloves)
	Input Configuration	Qwerty full keyboard, number / letter separate, professional custom smart input method
<b>GNSS Features</b>	GNSS	GNSS antenna, GPS, GLONASS, BDS, AGPS
<b>Communication Interface</b>	Network modem	FDD-LTE: B1/B3/B5/B7/B8/B20/B28/B2/B4/B12/B17
		TDD-LTE: B38/B39/B40/B41/B34
		TDSCDMA: B34/B39
		WCDMA: B1/B2/B5/B8/B4
		GSM: B2/B3/B5/B8
	CDMA1x/CDMA2000: BC0	
Cellular mobile	4G, Dual Nano-SIM	
WiFi	IEEE 802.11 a/b/g/n/ac, Wapi, AP (2.4G / 5G)	
Bluetooth	BT5.1, BLE, NFC	
USB	USB Type-C interface, OTG, supports fast charging (5V,3A)	
<b>Power Supply</b>	Battery	9200 mAh internal
	Duration	≥15 hours
	Charging time	4 h (typical)
<b>Application</b>	Camera	Built-in 13 million pixel camera, with laser to replace front camera
	Flash	Highlight Flash LED flash (support flashlight function)
	Sensor	Gravity sensor, compass, light sensor, gyroscope
<b>Physical Features</b>	Weight	406g (within battery)
	Size	221 mm*78 mm*16.5 mm
	Operating temperature	-30 C ~ +60 C
	Storage temperature	-40 C ~ +80 C
	Free fall	1.8 m
	Laser <sup>1</sup>	0.6-20m Accuracy: 10mm 20-40m Accuracy: 30mm
	Shock and vibration	MIL-STD-810H

Descriptions and Specifications are subject to change without notice

1.Suitable for indoor scenes, not suitable for high-precision ranging in strong light environments



AUTHORIZED DISTRIBUTION PARTNER

IP68

23J206

### Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, North of Panyu RD, Panyu District, 511400 Guangzhou, China.  
www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn